

RP 4150 | THERMAL PRINTER

Expand your vision



Versatile roll capacity up to 112 mm (4 inch width)
- Prints wider & bigger




High capacity paper width roll up to 102 mm - Paper roll need not be changed often



Standard dual interface of parallel & usb - Multiple connectivity option



Built-in auto cutter - Cuts the bills at the end of the print



Built-in power adapter - Sleek design to improve aesthetics

The RP 4150 Advantage

With the ever increasing customer demand for better clarity of bills, printing wider bills has become the need of the hour. Certain segments of retailers today prefer to expand the size of the bill from 3" to 4" (40 col to 60 col). RP 4150 is specifically designed for customers who want wider bills with superior quality. With a print speed of 150 mm/sec and an inbuilt auto cutter, it enables smooth flow of bills. With a capacity to hold a paper roll diameter of 102 mm, it reduces the need to change the paper roll frequently and therefore ensures hassle-free operations. It also comes with a standard built-in USB and parallel interface giving the user multiple connectivity options.

All this comes from a brand that has been the epitome of trust - TVS Electronics, a company which has understood the Indian retailer like no other.

Specifications

- Printing Method : Direct thermal
- Printing Speed : 150 mm / sec
- Dot Density : 203 dpi
- Dot Pitch : 8 x 8 dots / mm
- Character Per Line : Font A - 69 columns; Font B - 92 columns; Font C - 104 columns [at 112 mm paper width]
- Character Set : Alphanumeric, International, PC437 PC850 / 852 / 857 / 858 / 860 / 863 / 864 / 865 / 866
- Barcode Fonts : UPC-A/E, JAN(EAN) 13/8 columns, ITF, CODE 39, CODE 128, CODABAR (NW-7), CODE 93, PDF417, QR code
- Paper Width : 112 mm
- Paper Thickness : 0.065 - 0.15 mm
- Paper Roll Diameter : Max. ~102 mm

- Printing Width : 104 mm / 832 dots
- Interface : Parallel, USB
- Optional : Serial
- User Memory : 384 KB (capable of storing user-defined characters and logos)
- Buffer Size : 4 KB / 45 bytes in parallel; 16 KB in USB
- Emulation : ESC / POS
- Driver : Windows 7, Vista, 2K, XP, Linux, OPOS, VCOM
- Cash Drawer : 1 port
- Reliability (Print Head Life) : 100 km
- Physical Dimensions (W x D x H) mm : 177 x 213 x 147
- Auto Cutter Life : 1 million cuts
- Cutting Method : Full / partial cut
- Supply Voltage : AC 100 ~ 240V, 50 ~ 60Hz; DC 24V ± 7%
- Operating Temperature : 5° to 45°C
- Storage Temperature : -20° to 60°C
- Operating Humidity: 10% to 90% RH
- Storage Humidity : 10% to 90% RH
- Certifications : FCC, CE
- Features : Wall mountable, built-in AC adapter
- Warranty : 1 year

CUSTOMER SEGMENTS



Textile Shops



Jewellery Stores



Cinema Theatres



Amusement parks



Hypermarkets/ Supermarkets

ORDERING INFORMATION

OPTIONAL ACCESSORY

RP 4150 SERIAL CARD

DEALER STAMP