



THE TOUCHPOINT OF INDIA




LP 46 LABEL PRINTER

Desktop label printer




4-in-1 Connectivity -
Ethernet, USB, Serial and
Parallel interfaces



High Memory Capacity
- 8 MB SDRAM & 4 MB
Flash Memory and slot for
memory expansion



Turbo Print Speed -
6 inches per second for
quick label and tag printing



**Movable Black Mark
Sensor** - Ideal application
for printing cinema /
theater tickets



Small Foot Print -
Compact design, saves
space



Simple To Operate - Easy
& quick consumables
(ribbon & tags)
replenishment

The LP 46 Advantage

LP 46 is designed to withstand tough Indian POS environments where wide varying voltage and dusty conditions are a common feature - protecting the life of your investment.

4-in-1 Connectivity - Ethernet, USB, RS-232 serial and Centronics Parallel

High Memory Capacity - LP 46 printer comes with 8 MB SDRAM, 4 MB flash memory

Turbo Print Speed - Print speed of 6 inches per second and a 200 MHz 32-bit processor

Movable Black Mark Sensor - LP 46 has the unique capability of sensing black mark on labels and receipts, making it the ideal printer for printing cinema / theatre tickets

Specifications

Operational

Printing Method	: Direct thermal and thermal transfer
Print Speed	: Up to 6 ips
Resolution	: 203 dpi
Max. Print Width	: 108 mm (4.25")
Max. Print Length	: 2,286 mm (90")
Physical Dimensions	: 258 x 202 x 173 (L x W x H) mm

Ribbon Specifications

Capacity	: 110 m
Core	: 0.5
Max Outer Diameter	: 67 mm
Label Roll Capacity	: 127 mm (5") OD
Processor	: 32 bit RISC CPU
Memory	: 4 MB Flash; 8 MB SDRAM (SD card slot for memory expansion)
Interface	: Ethernet, USB, Parallel and Serial
Power Supply	: External universal switching power supply
Operation Switch, Button, LED	: One power switch, one feed button, one LED (3 colours: green, amber and red)

Sensors & Fonts

Sensors	: Gap transmissive sensor Moveable black mark reflective sensor Head open sensor Ribbon end sensor
Internal Font	: Eight alpha-numeric bitmap fonts, One Monotype Imaging CG Triumvirate Bold Condensed scalable font, Built-in Monotype True Type font engine

Barcode Font

1D Barcode	: Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET
2D Barcode	: PDF-417, Maxicode, Datamatrix, QR Code
Font & Barcode Rotation	: 0, 90, 180 & 270
Printer Language	: TSPL - EZ

Media

Media Type	: Continuous, die-cut, fanfold, linerless (DT only)
Media Wound Type	: Outside wound
Media Width	: 25.4 ~ 112 mm (1 ~ 4.4)
Media Thickness	: 0.06 ~ 0.19 mm (2.3 ~ 7.4 mil)
Media Core Diameter	: 25.4 ~ 38.1 mm (1 ~ 1.5)
Safety Regulation	: FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/GS, CCC

Accessories

: Bartender ultraLite labeling software driver
CD disk, Quick start guide, USB cable, External universal switching power supply, Power cord

Best suited for printing

Retail | Cinema / Theatres | Healthcare | Warehouse |
Transports & Logistics | Insurance & Finance | Shipping

CUSTOMER SEGMENTS

Amusement Parks	Hospitals	Couriers	Jewellery
Apparels	Library	Supermarket	Cinemas / Theatres

